Technical data sheet

Descriptions	Name Line Description Mounting possibilities Turning direction	X23 Bath Xower Bath 1-part movable bath wall at 180° Not possible to combine 90° outwards and 90° inwards	with a wall profile	
Measurement s	Article	Width	Height	Left/Right
	X23 001 000 ###	700 mm	1500 mm	Left/Right
	Made to measure Glass beveling	Not possible Not possible		
SS	Glass specifications	6mm toughened safety glass (norm NBN 23-002, klasse NBN EN 12600) 101 Transparant Not applicable		
Glass	Type of glass Glass treatment			
Finishing	Characteristics	Wall profile withlift extension Water barrier profile		27mm 27mm
	Finishings	Shiny (011), Black matte (099)		200
ė,	Stabilisation bar Measuring	Not applicable Not possible		
Service	Mounting Mounting instructions	Possible with price supplement Available		
8	Characteristics	UV-resistant according to Xenon test 1200 with cycle 120/18 Crystal-clear color according to RAU-PVC1107 Mold resistance according to DIN 5373		
Seals				
Technical details	Advice	Adjustability in the profile 20 mm (dimensions between 700 mm and 720 mm) A profile or glass must always be placed on the tiling. Otherwise, this can lead to issues with waterproofing. When preparing, take into account the size and weight of the glass. Can the glass be brought into and installed in the bathroom.		



Tel.: +32 (0)3 296 03 03