


Technical data sheet



Descriptions	Name	155 Master Concept		
	Line	Personal		
	Descriptions	Swinging door at 180° with 2 fixed panels		
	Mounting possibilities	Can be installed between 2 walls Can be combined with 160/161		
	Turning direction	90° inwards and 90° outwards		
Measurements	Article	Width	Height	Left/Right
	155 001 001 ###	up to 800 mm	up to 2000 mm	Left
	155 002 001 ###	801 mm-900 mm	up to 2000 mm	Left
	155 003 001 ###	901 mm-1000 mm	up to 2000 mm	Left
	155 004 001 ###	1001 mm-1200 mm	up to 2000 mm	Left
	155 005 001 ###	1201 mm-1400 mm	up to 2000 mm	Left
	155 006 001 ###	1401 mm-1600 mm	up to 2000 mm	Left
	155 007 001 ###	1601 mm-1800 mm	up to 2000 mm	Left
	155 008 001 ###	1801 mm-2000 mm	up to 2000 mm	Left
	155 009 001 ###	2001 mm-2500 mm	up to 2000 mm	Left
	155 001 002 ###	up to 800 mm	up to 2000 mm	Right
	155 002 002 ###	801 mm-900 mm	up to 2000 mm	Right
	155 003 002 ###	901 mm-1000 mm	up to 2000 mm	Right
	155 004 002 ###	1001 mm-1200 mm	up to 2000 mm	Right
	155 005 002 ###	1201 mm-1400 mm	up to 2000 mm	Right
	155 006 002 ###	1401 mm-1600 mm	up to 2000 mm	Right
	155 007 002 ###	1601 mm-1800 mm	up to 2000 mm	Right
	155 008 002 ###	1801 mm-2000 mm	up to 2000 mm	Right
	155 009 002 ###	2001 mm-2500 mm	up to 2000 mm	Right
		Made to measure	Made to measure per mm, max. width 2500mm. Extra height with additional costs	
	Glass beveling	Included		
Glass	Glass specifications	8 mm toughend safety glass (norm NBN 23-002, klasse NBN EN 12600)		
	Type of glass	101 Transparent	107 Green	119 Opal white
		130 Timeless	108 Blue	120 Opal Black
		102 Opal mat	114 Crepi	125 Opal bronze
		104 Extra transparent	115 Cathedral	126 Opal gris
		105 Bronze	118 Black	121 Mirror
		106 Gris		
	Glass treatments	109 Aquaclean	110 Zone intime	111 Zone à la carte
Bestag	Characteristics	4 glasvlakke muurklemmen, 2 glasvlakke scharnieren met liftfunctie, vierkante glasvlakke knop		
	Finishing ###	Shiny (011), Matte (001), Black matte (099) Other colors on demand		
	Stabilizing bar	2 stabilisation bars at 45°		
Service	Checking of measurements	Included in the price		
	Mounting	Possible at an additional cost		
	Mounting guidelines	Available		
Seals	Characteristics	Magnetic seals, intermediate seals and bottom seals		
		UV-resistant according to Xenon test 1200 with cycle 120/18 Crystal-clear color according to RAU-PVC1107 Mold resistance according to DIN 5373		
Technical details	Advice	A profile or glass must always be placed on the tiling. Otherwise, this can lead to issues with waterproofing. When preparing, take into account the size and weight of the glass. Can the glass be brought into and installed in the bathroom.		


Technical parts

155 Master Concept

Hinges



Doorknob



Wall Clamps



