## Technical data sheet

	Name Line	140 INV Sky Concept Personal		
Descriptions	Descriptions	Side panel attached IN ceiling with profile against the wall (Without profile)		
	Procedure	The profile is delivered at full length (2000mm)  Delivered to the whole saler  The profile is cut to size and installed by the professional according to the provided manual.  Aquaconcept will be informed when the measurement can take place.  Aquaconcept measures and manufactures glass		
	Mounting possibilities	Can be installed freestanding Can be combined with 140 INV (corner connection with UV bonding possible - Ref 933.999.999)		
	Article	Width	Height	Left/Right
Measurements	Basic profile			
	140 900 000 ###	2000 mm		
	Glass + finishing profile			
	140 407 001 ###	up to 500 mm	up to 2700 mm	Left
	140 408 001 ###	501 mm-800 mm	up to 2700 mm	Left
	140 401 001 ###	801 mm-1000 mm	up to 2700 mm	Left
	140 402 001 ### 140 403 001 ###	1001 mm-1200 mm 1201 mm-1400 mm	up to 2700 mm up to 2700 mm	Left Left
	140 403 001 ###	1401 mm-1600 mm	up to 2700 mm	Left
	140 405 001 ###	1601 mm-1800 mm	up to 2700 mm	Left
	140 406 001 ###	1801 mm-2000 mm	up to 2700 mm	Left
	140 401 002 ###	up to 500 mm	up to 2700 mm	Right
	140 402 002 ###	501 mm-800 mm	up to 2700 mm	Right
	140 401 002 ###	801 mm-1000 mm	up to 2700 mm	Right
	140 402 002 ###	1001 mm-1200 mm	up to 2700 mm	Right
	140 403 002 ###	1201 mm-1400 mm	up to 2700 mm	Right
	140 404 002 ### 140 405 002 ###	1401 mm-1600 mm 1601 mm-1800 mm	up to 2700 mm up to 2700 mm	Right Right
	140 406 002 ###	1801 mm-2000 mm	up to 2700 mm	Right
	Made to measure Glass beveling	Made to measure per mm, max. width 2000mm. Extra height with additional costs Included		
	Glass specifications	10 mm toughend safety glass (norm NBN 23-002, klasse NBN EN 12600)		
	Type of glass	101 Transparant	106 Gris	120 Opal Black
	71 - 1 - 3 ·····	130 Timeless	107 Green	125 Opal bronze
Glass		102 Opal mat	114 Crepi	126 Opal gris
છું		104 Extra transparant	118 Black	121 Mirror
		105 Bronze	119 Opal white	
	Glass treatments	109 Aquaclean 112 Print	110 Zone intime	111 Zone à la carte
υď	Characteristics	Invisible, profile recessed in the ceiling		
Finishing		with finishing profile  Vast plafond Flafond fix		
	Finishing ###	Shiny (011), Black matte (099), white matte (088)		
	Stabilizing bar	Not possible		
<u>ic</u>	Checking of measurements	Included in the price Possible at an additional cost - Mandatory for UV bonding		
Service	Mounting guidelines			
	Mounting guidelines	Available  Builtputlet   postil de base   Kompondet   postil de faste   Postil de faste		
Technical Details	Advice	A profile or glass must always be placed on the tiling.  Otherwise, this can lead to issues with waterproofing.		
		If it turns out that the profile cannot be built in		
		If it turns out that the profile cannot be built in.  This profile can also be used for surface mounting		
		When preparing, take into account the size and weight of the glass.  Can the glass be brought into and installed in the bathroom.		