
Technical data sheet

SUC
otic
ĊŢ
Ses
_

Name Line	X19 Slide Light Comfort
Description	Side panel that has to be combined with X09
Mounting possibilities	Has to be combined with X09



S	
نت	
_	
~	
Ψ	
⊏	
_	
a)	
_	
~	
<u>~</u>	
10	
Ψ	
<	

Article	Width	Adjustability	Height
X19 001 000 ###	800 mm	770 - 795 mm	2000 mm
X19 002 000 ###	900 mm	870 - 895 mm	2000 mm
X19 003 000 ###	1000 mm	970 - 995 mm	2000 mm
Made to measure	Not possible		

Made to measure Glass beveling

Not possible 6 mm toughened safety glass (norm NBN 23-002, klasse NBN EN 12600)

Type of glass
Glass treatment

101 Transparent 109 Aquaclean

Finishing

Glass

aracteristics Wall Profile

Profile on top of the glass

Shiny (011), White matte (088), Black matte (099)

Service

Measuring

Mounting

Possible with price supplement
Possible with price supplement
Available

Characteristics

UV-resistant according to Xenon test 1200 with cycle 120/18 Crystal-clear color according to RAU-PVC1107

Mold resistance according to DIN 5373

Technical details

Dichting


A profile or glass must always be placed on the tiling. Otherwise, this can lead to issues with waterproofing.


When preparing, take into account the size and weight of the glass.

Can the glass be brought into and installed in the bathroom.


Technical data sheet


Width 800mm





Width 900mm





Width 1000mm

