


Technical data sheet



Descriptions	Name	X29 Slide Light		
	Line	Comfort		
	Description	2-part sliding door, reversible		
Measurements	Mounting possibilities	Must be combined with X29 for cornerinstallation. Can be combined asymmetrically		
	Article	Width	Height	Entry
Glass	X29 001 000 ###	800 mm	765 - 790 mm	2000 mm
	X29 002 000 ###	900 mm	865 - 890 mm	2000 mm
Finishing	X29 003 000 ###	1000 mm	965 - 990 mm	2000 mm
	Made to measure	Not possible		
Service	Glass specifications	6 mm toughened safety glass (norm NBN 23-002, klasse NBN EN 12600)		
	Type of glass	101 Transparent		
	Glass treatment	109 Aquaclean		
Seals	Characteristics	Rail with integrated Soft Open and Close system at the top of the glass Click-out system at the bottom for easy maintenance		
	Hardware finish ###	Wall profile on fixed panel, water-resistant profile Shiny (011), White matte (088), Black matte (099)		
Technical details	Measuring	Possible with price supplement		
	Mounting	Possible with price supplement		
Seals	Mounting instructions	Available		
	Characteristics	UV-resistant according to Xenon test 1200 with cycle 120/18 Crystal-clear color according to RAU-PVC1107 Mold resistance according to DIN 5373		
Technical details	Advice	A profile or glass must always be placed on the tiling. Otherwise, this can lead to issues with waterproofing. When preparing, take into account the size and weight of the glass. Can the glass be brought into and installed in the bathroom.		