Technical data sheet

| | | recillicat dat | a sileet | _ |
|----------------------|--|--|---|--|
| Descriptions | Name Line Descriptions | 199-1 Steel Concept Personal Signle fixed panel without so Black or white steelconstruct | ction | |
| | Mounting possibilities | Can be mounted against the wall Can be combined with 191 or 199 (on request) | | |
| | Turning direction | Not possible | | |
| Measurements | Article | Height | Width | Left/Right |
| | 199 101 001 ### 199 102 001 ### 199 101 002 ### 199 102 002 ### | up to 1400mm 1401mm-1800mm up to 1400mm 1401mm-1800mm | up to 2000mm up to 2500mm up to 2000mm up to 2500mm | Left Left Right Right |
| < | Made to measure Glass beveling | Made to measure per mm, max. width 1800mm. Extra height with additional costs Not possible | | |
| Glass | Glass specifications Type of glass Glass treatments | 8 mm toughend safety glass 101 Transparent 130 Timeless 102 Opal mat 104 Extra transparent 105 Bronze 106 Gris 109 Aquaclean | (norm NBN 23-002, klasse NBN EN 12600) 107 Green 108 Blue 114 Crepi 115 Cathedral 116 Ribble 118 Black 110 Zone intime | 119 Opal White 120 Opal black 125 Opal bronze 126 Opal gris 121 Mirror |
| Finishing | Characteristics Finishing ### Stabilizing bar | Matte black or matte white construction Black matte (099), White matte (088) Stabilisation bar at 90° | | |
| Service | Checking of measurements Mounting Mounting guidelines | Included in the price Possible at an additional cost Available | | |
| Seals | Characteristics | UV-resistant according to Xenon test 1200 with cycle 120/18 Crystal-clear color according to RAU-PVC1107 Mold resistance according to DIN 5373 | | |
| Technical details | Advice | Hinges or glass must always be placed on the tiling. Otherwise, this can lead to issues with waterproofing. When preparing, take into account the size and weight of the glass. Can the glass be brought into and installed in the bathroom. | | |

